

MAESTRO

WHERE DURABILITY MEETS DESIGN

FINISH DESCRIPTION

High Performance Eggshell Paint + Primer

With industry-leading durability and a silky smooth eggshell finish, Maestro from Scuffmaster doesn't just enhance the beauty of your home, it protects it as well. Perfect for: Kitchens, bathrooms, hallways, mud rooms, and busy spaces.

FEATURES AND BENEFITS

Finish Effect	Rich, durable eggshell
Polyurethane Formulation	Exceptional durability and cleanability
Curated Colors	Set of 48 colors selected by leaders in fashion, retail, and interiors
Easy Application	Brush, roll or spray
Waterbased / Low VOC	Low odor application for easy install
Warranty	5 – Year manufacturer's warranty against adhesion failure if product is correctly applied

WHERE TO SPECIFY

Maestro High Performance Eggshell Paint is engineered for active spaces so it will succeed where other paints failed. Kitchens, bathrooms, hallways, and high-traffic areas in homes are the perfect place for Maestro.

Corporate Spaces

Corridors
Offices
Lobby areas
Conference rooms
Cafeterias
Lunch rooms
Bathrooms
Stairwells

Educational Facilities

Corridors
Offices
Lecture halls
Auditoriums
Gymnasiums
Locker rooms
Bathrooms
Dormitories

Healthcare Facilities

Corridors
Offices
Waiting areas
Examination rooms
Meeting rooms
Cafeterias
Bathrooms
Stairwells

Other Applications

Theaters
Exercise rooms
Pool areas
Escalator areas
Elevator areas
Passenger terminals
Baggage claim areas
Parking areas

Suitable Substrates:

Primed sheetrock, previously painted surfaces, concrete block, metal, ceramic tile, glazed block and others.

TECHNICAL INFORMATION

System Components	Finish Coat	
Finish Appearance	Rich eggshell	
Colors Available	48 curated designer colors.	
Colorant Systems	Compatible color formulas for Gennex, PPG, Novo II, LogiColor and Universal colorants	
Coverage Rates	Approximately 350 ft ² /gal. (deep/bright colors require additional coats)	
Maximum VOC	< 49 g/L	
Fire Rating	Class A or I	ASTM E-84-91a
Scrub Resistance:	2,300 Scrub Cycles	ASTM D 2486

FIVE YEAR LIMITED WARRANTY

ICP Building Solutions Group warrants the components of this finish system against manufacturing defect for a period of five years from the date of application when applied to a wall surface according to manufacturer's printed instructions. Manufacturing defect is defined to be a failure of the coating system to adhere to a wall surface when applied according to manufacturer's printed instructions, and does not include subsequent failure or damage caused by exogenous factors such as substrate failure or defect, sharp objects, persons, or acts of God. In the event of a failure resulting from manufacturing defect, the product will be replaced. ICP Building Solutions Group shall have no obligation to or otherwise participate in labor or other costs associated with replacing the product. This warranty supersedes all previous warranties.

SAFETY INFORMATION

Some persons may experience an allergic reaction to paint products if exposed to spray mist. Because spray application of this Scuffmaster finish may create a fine mist of product and product catalyst in the immediate application area, a high-efficiency particulate respirator and protective glasses or goggles should be worn by the applicator. The immediate application area should be "cautioned-off" to prevent persons without safety equipment from coming into contact with mist. Ensure good ventilation. Product SDS sheets are available at ICPGROUP.com

If medical advice is needed, have product container or label at hand. KEEP OUT OF REACH OF CHILDREN. Obtain special instructions before use. Wear protective gloves/protective clothing/eye protection/face protection. IF exposed or concerned: Get medical advice/attention. Wash contaminated clothing before reuse. Store locked up. Dispose of contents/container in accordance with local regulations. FIRST AID: EYE CONTACT: If this product comes in contact with eyes: Wash out immediately with water. If irritation continues, seek medical attention. Removal of contact lenses after an eye injury should only be undertaken by skilled personnel. SKIN CONTACT: Immediately remove all contaminated clothing, including footwear. Flush skin and hair with running water (and soap if available). Seek medical attention in event of irritation. INHALATION: If fumes, aerosols or combustion products are inhaled remove from contaminated area. Other measures are usually unnecessary. INGESTION: Immediately give a glass of water. First aid is not generally required. If in doubt, contact a Poisons Information Center or a doctor.

FINISHES FOR PROPERLY PREPARED SURFACES

1. New Sheetrock:

Primer - 1 coat quality acrylic primer
1-2 coats of Maestro High Performance Eggshell Paint

2. Cured Concrete/Masonry:

Primer - 1 coat of 100% latex acrylic block filler (if required to seal surface for better coverage)
1-2 coats of Maestro High Performance Eggshell Paint

3. Wood

Primer – Spot-prime knots and prime with 1 coat of a suitable stain-blocking primer
1-2 coats of Maestro High Performance Eggshell Paint

4. Hard Shiny Surfaces:

Primer - 1 coat quality acrylic bond promoting primer
1-2 coats of Maestro High Performance Eggshell Paint

5. Previously Painted Surfaces:

1-2 coats of Maestro High Performance Eggshell Paint

CLEANING INSTRUCTIONS

Allow product to cure for at least seven days following application (allow 28 days on hard, non-absorbent substrates) before applying cleaning chemicals. Most common stains can be removed using warm water and detergent. More difficult stains may require stronger cleaners and a light abrasive pad. Before using a new cleaner for the first time, test its effect on the finish by applying in an inconspicuous area as a small amount of paint may also be removed during the cleaning process.