

MAESTRO

WHERE DURABILITY MEETS DESIGN

FINISH DESCRIPTION

High Performance Stone Effect Paint

Maestro Stone Effect Paint creates a unique and natural blend of colors with unbeatable hide to conceal the imperfections in walls and feature spaces to keep them looking better longer - with much less maintenance - than ordinary paints and coatings.

FEATURES AND BENEFITS

Finish Effect	Roller applied, stone effect
Formulation	Exceptional durability and cleanability
Curated Colors	Set of 12 stock colors selected by leaders in fashion, retail, and interiors
Easy Application	Roller applied using specialty Maestro Stone Effect roller cover
Waterbased / Low VOC	Low odor application for easy install
Warranty	5 – Year manufacturer’s warranty against adhesion failure if product is correctly applied

WHERE TO SPECIFY

Maestro High Performance Stone Effect Paint is engineered for active spaces so it will succeed where other paints failed. Kitchens, bathrooms, hallways, and high-traffic areas in homes are the perfect place for Maestro.

Corporate Spaces

Corridors
Offices
Lobby areas
Conference rooms
Cafeterias
Lunch rooms
Bathrooms
Stairwells

Educational Facilities

Corridors
Offices
Lecture halls
Auditoriums
Gymnasiums
Locker rooms
Bathrooms
Dormitories

Healthcare Facilities

Corridors
Offices
Waiting areas
Examination rooms
Meeting rooms
Cafeterias
Bathrooms
Stairwells

Other Applications

Theaters
Exercise rooms
Pool areas
Escalator areas
Elevator areas
Passenger terminals
Baggage claim areas
Parking areas

Suitable Substrates:

Primed sheetrock, previously painted surfaces, concrete block, metal, ceramic tile, glazed block and others.

TECHNICAL INFORMATION

System Components	Finish Coat
Finish Appearance	Lightly textured, stone-like, multicolor
Colors Available	12 curated designer colors.
Colorant Systems	Stock colors tinted at the manufacturing facility
Coverage Rates	Up to 160 ft ² /gal. (Some colors require additional coats)
Maximum VOC	< 50 g/L
Fire Rating	Class A or I ASTM E-84-91a
Scrub Resistance:	3,000 Scrub Cycles ASTM D 2486
Solids By Volume	34.0%
Solids By Weight	5-40%
Dry Film Thickness	Average 5.0 mils.
Gloss	Flat (@ 60° angle)
Shelf Life	6 months from ship date
DOT Class	Not Regulated

SAFETY INFORMATION

Some persons may experience an allergic reaction to paint products if exposed to spray mist. Because spray application of this Scuffmaster finish may create a fine mist of product and product catalyst in the immediate application area, a high-efficiency particulate respirator and protective glasses or goggles should be worn by the applicator. The immediate application area should be "cautioned-off" to prevent persons without safety equipment from coming into contact with mist. Ensure good ventilation. Product SDS sheets are available at ICPGROUP.com

HARMFUL IF INHALED. CAUSES EYE SERIOUS IRRITATION. MAY CAUSE AN ALLERGIC SKIN REACTION.
PRECAUTIONS: Do not handle until all safety precautions have been read and understood. Avoid breathing dust/fume/gas/mist/vapors/spray. Use in a well-ventilated area. Close container after each use. Wear protective gloves/protective clothing/eye protection/face protection. **KEEP OUT OF THE REACH OF CHILDREN.** **FIRST AID:** Get medical advice/attention in any first aid situation. **IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue Rinsing. If irritation persists: get medical advice. **SKIN:** Remove contaminated clothing. Wash with plenty of soap and water. **INHALATION:** Remove person to fresh air. If not breathing give artificial respiration. If breathing is difficult, give oxygen. **INGESTION:** If swallowed, do not induce vomiting, immediately call a poison control center or a doctor/physician. See Safety Data Sheet for further information. **Storage:** Keep locked up. Store in a well-ventilated place. Keep container tightly closed. Dispose of contents in accordance with applicable local/national/regional/international regulations.

APPLICATION GUIDELINES

1. New Sheetrock:

Primer - 1 coat quality acrylic primer
1-2 coats of Maestro High Performance Eggshell Paint

2. Cured Concrete/Masonry:

Primer - 1 coat of 100% latex acrylic block filler (if required to seal surface for better coverage)
1-2 coats of Maestro High Performance Eggshell Paint

3. Wood

Primer – Spot-prime knots and prime with 1 coat of a suitable stain-blocking primer
1-2 coats of Maestro High Performance Eggshell Paint

4. Hard Shiny Surfaces:

Primer - 1 coat quality acrylic bond promoting primer
1-2 coats of Maestro High Performance Eggshell Paint

5. Previously Painted Surfaces:

1-2 coats of Maestro High Performance Eggshell Paint

APPLICATION INFO

Method	Rolled in accordance to manufacturer's published application instructions.
Drying Time	Approximately 2 hours to recoat @ 70° F and 50% relative humidity. Full cure within 7-10 days.
Thinning	Do Not Thin
Tinting	Do Not Tint
Clean Up	Warm soapy water.

FIVE YEAR LIMITED WARRANTY

ICP Building Solutions Group warrants the components of this finish system against manufacturing defect for a period of five years from the date of application when applied to a wall surface according to manufacturer's printed instructions. Manufacturing defect is defined to be a failure of the coating system to adhere to a wall surface when applied according to manufacturer's printed instructions, and does not include subsequent failure or damage caused by exogenous factors such as substrate failure or defect, sharp objects, persons, or acts of God. In the event of a failure resulting from manufacturing defect, the product will be replaced. ICP Building Solutions Group shall have no obligation to or otherwise participate in labor or other costs associated with replacing the product. This warranty supersedes all previous warranties.